



SENSORS WITH CONNECTION HEADS

Configuration Code GP04 Spring-Loaded MgO Thermocouple/Thermowell Assemblies with Explosion-Proof Connection Heads

Spring-Loaded MgO Thermocouple/Thermowell Assemblies with Explosion-Proof Connection Heads are designed for use with various thermowell types. Complete assemblies can be ordered by selecting the MgO assembly below, the thermowell from the thermowell section of the catalog, and a temperature transmitter from the back of this section. Assemblies without a thermowell can be ordered by selecting the sensor assembly from this page and inserting the "S" length in table 2-0. These sensors are supplied with a 316 stainless steel sheath and as standard limits or error.



ORDER CODES

Example Order Number:

1-0 1-1 1-2 2-0 3-0 4-0 4-1 4-2
J 48 U - Select Thermowell Part # or Insert 3 Digit Length Code - **SL** - **8XU4 93, T** Select Type and Range from back of section

1-0 Thermocouple Types

CODE		
SINGLE	DUPLEX	TRIPLEX
E	EE	-
J	JJ	JJJ
K	KK	KKK
T	TT	-

1-1 Sheath Diameters

CODE	DIAMETERS (inches) 316 SS
38	3/16
48	1/4

1-2 Measuring Junction

CODE	DESCRIPTION
G	Grounded junction
U	Ungrounded junction

2-0

Select thermowell part number from Thermowell Section, or specify 3 digit "S" length in inches if no thermowell is required.

3-0 Element Options

CODE	DESCRIPTION
SL ^[1]	Spring-loaded element
SC	Self-contained spring-loaded element
SN	Self-contained spring-loaded element with Buna-N oil seal 121°C [250°F] 100 PSI Max.
[1] Not available with option 75T	

4-0 Head Mounting Fittings

CODE	DESCRIPTION
STEEL FITTINGS	
6HN	1/2" x 1/2" NPT hex nipple 1" "E" length
6PN_	1/2" NPT pipe nipple (specify "E" length in inches)
6XU_ ^[1]	1/2" NPT union/nipple (specify "E" length in inches)
316 SS FITTINGS	
8HN	1/2" x 1/2" NPT hex nipple 1" "E" length
8PN_	1/2" NPT pipe nipple (specify "E" length in inches)
8XU_ ^[1]	1/2" NPT union/nipple (specify "E" length in inches)
[1] 3 1/2" Minimum length required	

4-1 Head Terminations

CODE	DESCRIPTION
74	Dual conduit DIN form B aluminum explosion-proof/flame-proof head, NEC, IEC, Atex approved
75T142C	(4 to 20) mA HART® field transmitter with aluminum explosion-proof housing
93	Aluminum explosion-proof/flame-proof head, NEC, IEC, Atex approved
94	316L stainless steel explosion-proof/flame-proof head, NEC, IEC, Atex approved

4-2 Options

SB	1/2" NPT conduit reducer bushing
I	Stainless tag
T71-00	(4 to 20) mA isolated programmable transmitter
T72-00	(4 to 20) mA isolated programmable HART® transmitter
T82-00	(4 to 20) mA Dual input, isolated HART® head-mounted transmitter

See transmitter ordering information in back of section.

HART® is a registered trademark of HART Communication Foundation.

