


# HAZARDOUS LOCATION

## Configuration Code XP06 Hazardous Location Flame-Proof-Certified, Spring-Loaded Thermocouple Assemblies

Flame-Proof, Spring-Loaded Thermocouples are made for use in IEC hazardous areas. They are designed to extinguish flames inside the device, eliminating the potential for ignition of flammable mixtures in the surrounding atmosphere. ATEX and IECEx certified assemblies are rated for Ex db IIC Gb and Ex tb IIIC Db locations for applications with process temperatures of 180 °C or less. The assemblies feature 316 stainless steel sheaths and ungrounded isolated junctions. They are available with aluminum or stainless steel explosion-proof connection heads. Note: The "S" dimension will measure 1/4" longer than specified when the spring is in the relaxed position. The "S" dimension is calculated when the sensor is compressed or in the installed position. This design allows 1/4" spring compression to ensure positive contact with the bottom of the thermowell.



### ORDER CODES

**Example  
Order Number:**

1-0 2-0 2-1 2-2 3-0 4-0 5-0 5-1 5-2  
**HL06 - J 48 U - 012 - FP - 8HN 94, T** Select Type and Range from back of Section

#### 1-0 Agency Approval

CODE	DESCRIPTION
HL06	ATEX/IECEx flame-proof-certified assembly

#### 2-0 Thermocouple Types

CODE		
SINGLE	DUPLEX	TRIPLEX
E	EE	-
J	JJ	JJJ
K	KK	KKK
T	TT	-

#### 2-1 Sheath Diameters 316 SS

CODE	DIAMETER (inches)
48	1/4

#### 2-2 Measuring Junction

CODE	DESCRIPTION
U	Ungrounded

#### 3-0 "S" Dimensions

Insert three digit sheath length ("S" Dimension) in inches

#### 5-1 Head Terminations

CODE	DESCRIPTION
75T142E	(4 to 20) mA HART® Field Transmitter with aluminum flame-proof housing
76T71-D10	(4 to 20) mA isolated programmable transmitter with digital display and explosion-proof aluminum housing
76T72-D10	(4 to 20) mA isolated programmable HART® transmitter with digital display and explosion-proof aluminum housing
76T82-D10	(4 to 20) mA dual input HART® Field Transmitter with digital display and explosion-proof aluminum housing
93	Aluminum flame-proof head
94	316L stainless steel flame-proof head

#### 5-2 Options

SB	1/2" NPT conduit reducer bushing, Aluminum
I	Stainless steel tag
M2	M20x1.5 conduit reducer bushing, Nickel Plated Brass
M5	M25x1.5 conduit reducer bushing, Nickel Plated Brass
T71-00	(4 to 20) mA isolated head-mounted transmitter
T72-00	(4 to 20) mA HART® isolated head-mounted transmitter
T82-00	(4 to 20) mA dual input, isolated HART® head-mounted transmitter

See transmitter ordering information in back of section.

#### 5-0 Head Mounting Fittings

CODE	DESCRIPTION
316 STAINLESS STEEL FITTINGS	
8HN	1/2" NPT hex fitting (1-1/2" "E" length)
8XU <sup>[1]</sup>	1/2" NPT union/nipple (specify "E" length in inches)
[1] 3 1/2" minimum length, maximum length is 9".	

#### 4-0 Element Options

FP	Spring-loaded element with flame path
----	---------------------------------------

HART® is a registered trademark of the HART Communication Foundation.

